SWC Product Overview

Bearing Range	Temperature Range			Speed Limit	Other Features
High Temp Bearings	HT1	HT2	HT3		
6000 - 6020	270° C to 350° C	150° C to 270° C	270° C to 320° C	max. 50 RPM	**Riveted Steel Cage**
6200 - 6220					**Superior Rust Protection with Manganese Phosphating**
6300 - 6320					
Maintenance Information	requires maintenace after 12-18 months in operation	under normal operating conditions , maintenance free for 3-5 years	maintenance free up to 6 years		

			Speed Limit		
Deep Groove Ball Bearings	**Standard**	**Suffix T250**	**Standard**	**Suffix T250**	
6000 - 6020	up to 200° C	up to 250° C	as per Catalogue Table	Yes, for T250 **	**Riveted Steel Cage**
6200 - 6220					**Same price for CN, C3 or C4**
6300 - 6320					
Radial Insert Ball Bearing Units	**Standard**	**Suffix T250**	**Standard**	**Suffix T250**	
UCP204-212, metric or inch sizes	up to 200° C	up to 250° C	as per Catalogue Table	Yes, for T250 **	**Riveted Steel Cage**
UCF204-212, metric or inch sizes					**Superior Rust Protection with Manganese Phosphating**
UCFL204-212, metric or inch sizes					
SEALED Spherical Roller Bearings	**Standard**	**Suffix T250**	**Standard**	**Suffix T250**	
BS22208-2VS - BS22222-2VS	up to 200° C	up to 250° C	as per Catalogue Table	Yes, for T250 **	**All Bearings with VITON Seals**
BS24122-2VS - BS24128-2VS					

** Please contact your local SWC Distributor/Representative, or contact us via email: info@swc-thailand.com